

TO TIE DOWN

1. Insert strap through slot A and take up slack
2. Push down and pull up handle B to work the ratchet until the strap is as tight as necessary
3. Push handle B down to lock. Your tie down is now locked.



TO RELEASE

1. Pull back on the quick release (C) and hold.
2. Pull handle B up and over to a fully open position
3. Pull tie-down up to loosen strap and remove strap from slot A.



WARNING

1. Please read and understand all instructions and warnings before using this product. Failure to do so could cause personal injury, damage to the product and/or personal property.
2. This is a consumable product. Always inspect nylon straps and buckle mechanisms before using. Exposure to outdoor elements will eventually cause deterioration. Do not use if the tie downs are cur, worn and/or frayed.
3. Always store indoors when not in use
4. Maximum working load is 800 lbs. (362 kilos)
5. Never over tighten
6. Always stand clear of hook and strap rebound path when applying load.
7. This product is not designed for towing, pulling, lifting or securing human weight.
8. Insure that area of attachment is of sufficient strength to withstand strap tension or unexpected load shifts during transportation.
9. Never use additional bats, levers, etc. to apply tension.
10. When securing boats or jet skis, always use in conjunction with a winch, rope, cable, strap or locking bolt.
11. Texsport is not responsible or liable for accidents or injured caused by product deterioration, product neglect or improper use.
12. Caution and sound judgement must be exercised when using this product.

MADE IN CHINA FOR TEXSPORT
HOUSTON, TX 77255
© 2004 TEXSPORT
www.texsport.com



ITEM 17048

